



HELICAL-BEVEL SHIPPING WEIGHTS & MOTOR COMPATIBILITY

REDUCER WEIGHTS (lbs) SOLID OUTPUT SHAFT

Size	Solid Input Shaft (Mounting Type A)	C-Frame Quill input (Mounting Type E)					
		56C	143TC 145TC	182TC 184TC	213TC 215TC	254TC 256TC	284TC 286TC
K8473	59	61	61	66	-	-	-
K8673	93	94	94	100	-	-	-
K8773	163	170	170	170	170	-	-
K8873	280	-	-	283	283	292	292
K8973	434	-	-	430	430	434	434
K8675	122	122	122	-	-	-	-
K8775	198	200	200	204	-	-	-
K8875	378	385	385	385	-	-	-

REDUCER WEIGHTS (lbs) HOLLOW OUTPUT SHAFT

Size	Solid Input Shaft (Mounting Type A)	C-Frame Quill input (Mounting Type E)					
		56C	143TC 145TC	182TC 184TC	213TC 215TC	254TC 256TC	284TC 286TC
K8473	56	58	58	63	-	-	-
K8673	89	90	90	96	-	-	-
K8773	154	161	161	161	161	-	-
K8873	265	-	-	268	268	277	277
K8973	407	-	-	403	403	407	407
K8675	118	118	118	-	-	-	-
K8775	189	191	191	195	-	-	-
K8875	363	370	370	370	-	-	-

Helical - Bevel
Gear Reducers

NEMA MOTOR FRAME AVAILABILITY - QUILL INPUT REDUCERS

Size	56C	143TC 145TC	182TC 184TC	213TC 215TC	254TC 256TC	284TC 286TC	324TC	364TC
K8473	X	X	X	-	-	-	-	-
K8673	X	X	X	-	-	-	-	-
K8773	X	X	X	X	-	-	-	-
K8873	-	-	X	X	X	X	-	-
K8973	-	-	X	X	X	X	-	-
K1073	-	-	X	X	X	X	X	X
K8675	X	X	-	-	-	-	-	-
K8775	X	X	X	-	-	-	-	-
K8875	X	X	X	-	-	-	-	-



Mounting position must be specified on all orders, and included in the reducer description, so the correct amount of oil is installed at the Factory.

MOUNTING POSITIONS

