

TOTALLY ENCLOSED AUTOMOTIVE DUTY • 56 FRAME



230/460 VOLTS • 3-PHASE
FOOT MOUNT & C-FACE
1/4 TO 3 HP

Features:

- NEMA Design B Performance
- Steel frame/cast aluminum end brackets
- Premium Class F Insulation system
- Continuous Duty
- Nameplated 1.15 service factor, 40°C ambient and 1.00 service factor, 65°C ambient.
- Warranty – 48 & 56 frames 12 months from date of first use or 18 months from date of manufacture or 12 months from date of installation, whichever period expires first.
- Made In U.S.A.



Applications:

Ideally suited for use on pumps, fans, conveyors, gear boxes and other equipment located in automotive manufacturing facilities.

FOOT MOUNT

HP	SYN RPM	Frame	FL Nom Eff (%)	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	List Price	Mult Sym
1/4	1800	56	68.0	1.15	230/460	SRN4H0.25T61	LM25123	AH	22	\$433	LJ-1
	1200	56	73.4	1.15	230/460	SRN6H0.25T61	LM25127	AH	28	618	LJ-1
1/3	3600	56	64.0	1.15	230/460	SRN2H0.33T61	LM25124	AH	20	389	LJ-1
	1800	56	68.0	1.15	230/460	SRN4H0.33T61	LM25115	AH	22	460	LJ-1
	1200	56	75.5	1.15	230/460	SRN6H0.33T61	LM25116	AH	29	625	LJ-1
1/2	3600	56	74.0	1.15	230/460	SRN2H0.5T61	LM25126	AH	23	418	LJ-1
	1800	56	77.0	1.15	230/460	SRN4H0.5T61	LM24258	AH	26	527	LJ-1
	1200	56	78.5	1.15	230/460	SRN6H0.5T61	LM24268	AH	42	690	LJ-1
3/4	3600	56	80.0	1.15	230/460	SRN2H0.75T61	LM25133	AH	34	479	LJ-1
	1800	56	81.5	1.15	230/460	SRN4H0.75T61	LM24266	AH	30	583	LJ-1
	1800	56	75.5	1.15	230/460	SRF4H0.75T61	LM25142	AH	25	935	LJ-1
	1200	56	74.0	1.15	230/460	SRF6H0.75T61	LM25148		29	544	LJ-1
1	3600	56	82.5	1.15	230/460	SRN2H1T61	LM25129	AH	41	539	LJ-1
	1800	56	77.0	1.15	230/460	SRF4H1T61	LM25113		28	458	LJ-1
	1200	56	78.5	1.15	230/460	SRF6H1T61	LM25130		37	578	LJ-1
1 1/2	3600	56	80.0	1.15	230/460	SRF2H1.5T61	LM25160		27	501	LJ-1
	1800	56	80.0	1.15	230/460	SRF4H1.5T61	LM25147		32	501	LJ-1
2	3600	56	80.0	1.15	230/460	SRF2H2T61	LM25161		31	578	LJ-1
	1800	56	82.5	1.15	230/460	SRF4H2T61	LM25159		46	578	LJ-1
3	3600	56	84.0	1.15	230/460	SRF2H3T61	LM25152		44	648	LJ-1

C-FACE WITH FEET

HP	SYN RPM	Frame	FL Nom Eff (%)	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	List Price	Mult Sym
1/4	1800	56C	68.0	1.15	230/460	SRN4H0.25TC61	LM25131	AH	22	\$477	LJ-1
	1200	56C	73.4	1.15	230/460	SRN6H0.25TC61	LM25135	AH	28	664	LJ-1
1/3	3600	56C	64.0	1.15	230/460	SRN2H0.33TC61	LM25153	AH	20	434	LJ-1
	1800	56C	68.0	1.15	230/460	SRN4H0.33TC61	LM25149	AH	22	506	LJ-1
	1200	56C	75.5	1.15	230/460	SRN6H0.33TC61	LM25164	AH	29	670	LJ-1

Product numbers in red are STOCK items.



TOTALLY ENCLOSED AUTOMOTIVE DUTY • 56 FRAME

230/460 VOLTS • 3-PHASE
FOOT MOUNT & C-FACE
1/4 TO 3 HP

C-FACE WITH FEET (cont'd)

HP	SYN RPM	Frame	FL Nom Eff (%)	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	List Price	Mult Sym
1/2	3600	56C	74.0	1.15	230/460	SRN2H0.5TC61	LM25151	AH	23	\$460	LJ-1
	1800	56C	77.0	1.15	230/460	SRN4H0.5TC61	LM25114	AH	26	572	LJ-1
	1200	56C	78.5	1.15	230/460	SRN6H0.5TC61	LM25134	AH	42	734	LJ-1
3/4	3600	56C	80.0	1.15	230/460	SRN2H0.75TC61	LM25119	AH	34	524	LJ-1
	1800	56C	81.5	1.15	230/460	SRN4H0.75TC61	LM25121	AH	30	629	LJ-1
	1200	56C	74.0	1.15	230/460	SRF6H0.75TC61	LM25141		30	589	LJ-1
1	3600	56C	82.5	1.15	230/460	SRN2H1TC61	LM25125	AH	41	583	LJ-1
	1800	56C	77.0	1.15	230/460	SRF4H1TC61	LM25117		29	504	LJ-1
	1200	56C	78.5	1.15	230/460	SRF6H1TC61	LM25150		37	624	LJ-1
1 1/2	3600	56C	80.0	1.15	230/460	SRF2H1.5TC61	LM25163		27	547	LJ-1
	1800	56C	80.0	1.15	230/460	SRF4H1.5TC61	LM25143		33	547	LJ-1
2	3600	56C	80.0	1.15	230/460	SRF2H2TC61	LM25145		32	624	LJ-1
	1800	56C	82.5	1.15	230/460	SRF4H2TC61	LM25156		46	624	LJ-1
3	3600	56C	84.0	1.15	230/460	SRF2H3TC61	LM25146		45	693	LJ-1

C-FACE FOOTLESS

HP	SYN RPM	Frame	FL Nom Eff (%)	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	List Price	Mult Sym
1/4	1800	56C	68.0	1.15	230/460	SRN4H0.25TCN61	LM25136	AH	21	\$477	LJ-1
	1200	56C	73.4	1.15	230/460	SRN6H0.25TCN61	LM25138	AH	28	664	LJ-1
1/3	3600	56C	64.0	1.15	230/460	SRN2H0.33TCN61	LM25158	AH	20	434	LJ-1
	1800	56C	68.0	1.15	230/460	SRN4H0.33TCN61	LM25128	AH	21	506	LJ-1
	1200	56C	75.5	1.15	230/460	SRN6H0.33TCN61	LM25155	AH	29	670	LJ-1
1/2	3600	56C	74.0	1.15	230/460	SRN2H0.5TCN61	LM25154	AH	22	460	LJ-1
	1800	56C	77.0	1.15	230/460	SRN4H0.5TCN61	LM24259	AH	26	572	LJ-1
	1200	56C	78.5	1.15	230/460	SRN6H0.5TCN61	LM25122	AH	42	734	LJ-1
3/4	3600	56C	80.0	1.15	230/460	SRN2H0.75TCN61	LM25139	AH	34	523	LJ-1
	1800	56C	81.5	1.15	230/460	SRN4H0.75TCN61	LM24262	AH	30	629	LJ-1
	1200	56C	74.0	1.15	230/460	SRF6H0.75TCN61	LM25137		29	589	LJ-1
1	3600	56C	82.5	1.15	230/460	SRN2H1TCN61	LM25112	AH	41	583	LJ-1
	1800	56C	77.0	1.15	230/460	SRF4H1TCN61	LM24271		28	504	LJ-1
	1200	56C	78.5	1.15	230/460	SRF6H1TCN61	LM25118		37	624	LJ-1
1 1/2	3600	56C	80.0	1.15	230/460	SRF2H1.5TCN61	LM25120		27	546	LJ-1
	1800	56C	80.0	1.15	230/460	SRF4H1.5TCN61	LM25140		32	546	LJ-1
2	3600	56C	80.0	1.15	230/460	SRF2H2TCN61	LM25165		31	624	LJ-1
	1800	56C	82.5	1.15	230/460	SRF4H2TCN61	LM25132		46	624	LJ-1
3	3600	56C	84.0	1.15	230/460	SRF2H3TCN61	LM25157		44	693	LJ-1

Prices and data subject to change without notice.

Product numbers in red are STOCK items.


TOTALLY ENCLOSED AUTOMOTIVE DUTY • U-FRAME



460 VOLTS • 3-PHASE
FOOT MOUNT & C-FACE
3/4 TO 100 HP

Features:

- Meets NEMA U-Frame dimensional and performance standards.
- Meets or exceeds General Motors GM-7EH and -7EQ, Ford EM1, and Chrysler NPEM-100 specifications.
- Full cast iron construction – all frame sizes.
- Oversized, cast iron terminal box complete with gaskets provides excellent protection from the environment. Also includes threaded conduit entry hole for easy power connection.
- NEMA Design B Performance.
- Nameplated 1.15 service factor, 40°C ambient and 1.00 service factor, 65°C ambient.
- Continuous Duty
- Inverter-Rated
- Premium Class F Insulation System.
- P efficiency codes comply with the United States' and Canadian efficiency requirements for general-purpose T-Frame industrial motors.
- Variety of configurations available – C-Face, D-Flange, double-shaft and brake.
- Lower noise designs improve plant sound quality.
- UL Recognized Component Listing and CSA Approval.
- Warranty –
(sine-wave power) 42 months from date of manufacture and 36 months from date of installation which ever period expires first.
(inverter power) 30 months from date of manufacture and 24 months from date of installation which ever period expires first.
- Shielded ball bearing for direct coupled applications. Contact your local sales office for belted applications.
- Made in U.S.A.



Applications:

Ideally suited for a wide variety of tough applications found in automotive manufacturing facilities and other industries utilizing U-Frame motors.

Speed ranges (continuous duty) on variable-frequency electronic speed controls (inverters):

P efficiency codes: Constant torque, 6 to 60 Hz
Variable torque, 3 to 60 Hz

G efficiency codes: Constant torque, 15 to 60 Hz
Variable torque, 6 to 60 Hz

Ask about wider speed ranges at intermittent duty.

Lincoln U-Frame motors exceed NEMA MG-1, Section IV, Part 31 spike resistance requirements.

FOOT MOUNT

HP	SYN RPM	Frame	FL Nom Eff (%)	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	List Price	Mult Sym
3/4	1200	182	82.5	1.15	460	CCN6P0.75U64	LM21379	AH	108	\$929	LU-1
	1200	182	81.0	1.00	460	CCN6G0.75U64	LM23722	AQ	108	721	LU-1
1	1800	182	87.5	1.15	460	CCN4P1U64	LM21378	AH	108	874	LU-1
	1800	182	86.0	1.00	460	CCN4G1U64	LM23721	AQ	108	677	LU-1
	1200	184	86.5	1.15	460	CCN6P1U64	LM21381	AH	108	1067	LU-1
	1200	184	85.0	1.00	460	CCN6G1U64	LM23726	AQ	108	827	LU-1
1 1/2	3600	182	85.5	1.15	460	CCN2P1.5U64	LM21084	AH	108	803	LU-1
	1800	184	88.8	1.15	460	CCN4P1.5U64	LM21380	AH	108	935	LU-1
	1800	184	87.0	1.00	460	CCN4G1.5U64	LM23724	AQ	108	726	LU-1
	1200	184	87.5	1.15	460	CCN6P1.5U64	LM20709	AH	108	1175	LU-1
	1200	184	86.0	1.00	460	CCN6G1.5U64	LM23725	AQ	108	914	LU-1
	2	3600	184	85.5	1.15	460	CCF2P2U64	LM21085	AH	120	885
1800		184	89.5	1.15	460	CCF4P2U64	LM20708	AH	120	984	LU-1
1800		184	88.0	1.00	460	CCF4G2U64	LM23723	AQ	170	765	LU-1
1200		213	87.5	1.15	460	CCF6P2U64	LM21383	AH	170	1303	LU-1
1200		213	86.0	1.00	460	CCF6G2U64	LM23728	AQ	170	1095	LU-1
3		3600	184	87.5	1.15	460	CCF2P3U64	LM20707	AH	120	1091
	1800	213	88.5	1.15	460	CCF4P3U64	LM21382	AH	170	1132	LU-1
	1800	213	87.0	1.00	460	CCF4G3U64	LM23727	AQ	170	960	LU-1
	1200	215	89.5	1.15	460	CCF6P3U64	LM20391	AH	170	1614	LU-1
	1200	215	88.0	1.00	460	CCF6G3U64	LM23730	AQ	170	1255	LU-1

Prices and data subject to change without notice.

Product numbers in red are STOCK items.



TOTALLY ENCLOSED AUTOMOTIVE DUTY • U-FRAME

460 VOLTS • 3-PHASE
FOOT MOUNT & C-FACE
3/4 TO 100 HP

FOOT MOUNT (cont'd)

HP	SYN RPM	Frame	FL Nom Eff (%)	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	List Price	Mult Sym
5	3600	213	87.5	1.15	460	CCF2P5U64	LM21086	AH	170	\$1208	LU-1
	1800	215	89.5	1.15	460	CCF4P5U64	LM20392	AH	170	1501	LU-1
	1800	215	88.0	1.00	460	CCF4G5U64	LM23729	AQ	170	1290	LU-1
	1200	254U	90.2	1.15	460	CCF6P5U64	LM21385	AH	260	2364	LU-1
	1200	254U	88.7	1.00	460	CCF6G5U64	LM23732	AQ	260	2099	LU-1
7 1/2	3600	215	88.5	1.15	460	CCF2P7.5U64	LM20393	AH	170	1454	LU-1
	1800	254U	91.7	1.15	460	CCF4P7.5U64	LM21384	AH	260	1972	LU-1
	1800	254U	90.2	1.00	460	CCF4G7.5U64	LM23731	AQ	260	1577	LU-1
	1200	256U	91.0	1.15	460	CCF6P7.5U64	LM20389	AH	332	2870	LU-1
	1200	256U	89.5	1.00	460	CCF6G7.5U64	LM23734	AQ	332	2293	LU-1
10	3600	254U	89.5	1.15	460	CCF2P10U64	LM21087	AH	260	1740	LU-1
	1800	256U	91.7	1.15	460	CCF4P10U64	LM20390	AH	260	2396	LU-1
	1800	256U	90.2	1.00	460	CCF4G10U64	LM23733	AQ	260	1916	LU-1
	1200	284U	91.0	1.15	460	CCF6P10U64	LM20028	AH	525	3518	LU-1
	1200	284U	89.5	1.00	460	CCF6G10U64	LM23736	AQ	525	2809	LU-1
15	3600	256U	91.7	1.15	460	CCF2P15U64	LM20394	AH	260	2217	LU-1
	1800	284U	92.4	1.00	460	CCF4P15U64	LM21665	AH	525	3290	LU-1
	1800	284U	90.9	1.00	460	CCF4G15U64	LM23735	AQ	525	2633	LU-1
	1200	324U	92.4	1.15	460	CCF6P15U64	LM21387	AH	750	4734	LU-1
	1200	324US	92.4	1.15	460	CCF6P15US64	LM21809	AH	750	4734	LU-1
	1200	324U	90.9	1.00	460	CCF6G15U64	LM23739	AQ	750	3782	LU-1
	1200	326U	92.4	1.15	460	CCF6P20U64	LM20031	AH	750	5784	LU-1
20	3600	286U	90.2	1.15	460	CCF2P20U64	LM21088	AH	525	3015	LU-1
	1800	286U	93.0	1.15	460	CCF4P20U64	LM20029	AH	525	4044	LU-1
	1800	286U	91.5	1.00	460	CCF4G20U64	LM23737	AQ	525	3232	LU-1
	1200	326U	92.4	1.15	460	CCF6P20U64	LM20031	AH	750	5784	LU-1
	1200	326US	92.4	1.15	460	CCF6P20US64	LM21812	AH	750	5784	LU-1
	1200	326U	90.9	1.00	460	CCF6G20U64	LM23741	AQ	750	4623	LU-1
	1200	364U	93.0	1.15	460	CCF6P25U64	LM21389	AH	1160	6983	LU-1
25	3600	324U	93.6	1.15	460	CCF2P25U64	LM21089	AH	748	3867	LU-1
	3600	324US	93.6	1.15	460	CCF2P25US64	LM21807	AH	748	3867	LU-1
	1800	324U	92.1	1.15	460	CCF4P25U64	LM21386	AH	748	5060	LU-1
	1800	324US	92.1	1.15	460	CCF4P25US64	LM21808	AH	748	5060	LU-1
	1800	324U	92.6	1.00	460	CCF4G25U64	LM23738	AQ	748	4044	LU-1
	1200	364U	93.0	1.15	460	CCF6P25U64	LM21389	AH	1160	6983	LU-1
	1200	364US	93.0	1.15	460	CCF6P25US64	LM21814	AH	1160	6984	LU-1
30	3600	364U	91.5	1.00	460	CCF6G25U64	LM23743	AQ	1160	5583	LU-1
	3600	326US	91.0	1.15	460	CCF2P30US64	LM21810	AH	748	4664	LU-1
	3600	326U	91.0	1.15	460	CCF2P30U64	LM21090	AH	748	4664	LU-1
	1800	326U	94.1	1.15	460	CCF4P30U64	LM20030	AH	748	5911	LU-1
	1800	326US	94.1	1.15	460	CCF4P30US64	LM21811	AH	748	5912	LU-1
	1800	326U	92.6	1.00	460	CCF4G30U64	LM23740	AQ	748	4725	LU-1
	1200	365U	93.0	1.15	460	CCF6P30U64	LM19531	AH	1160	7905	LU-1
40	3600	364US	93.6	1.15	460	CCF2P40US64	LM21091	AH	908	6092	LU-1
	3600	364U	93.6	1.15	460	CCF2P40U64	LM21798	AH	908	6092	LU-1
	1800	364U	94.1	1.15	460	CCF4P40U64	LM21388	AH	977	7794	LU-1
	1800	364US	94.1	1.15	460	CCF4P40US64	LM21813	AH	977	7795	LU-1
	1800	364U	92.6	1.00	460	CCF4G40U64	LM23742	AQ	977	6903	LU-1
	1200	404U	93.6	1.15	460	CCF6P40U64	LM21390	AH	1110	10181	LU-1
	1200	404US	93.6	1.15	460	CCF6P40US64	LM21817	AH	1110	10181	LU-1
1200	404U	92.1	1.00	460	CCF6G40U64	LM23746	AQ	1110	8135	LU-1	

Prices and data subject to change without notice.

Product numbers in red are STOCK items.

TOTALLY ENCLOSED AUTOMOTIVE DUTY • U-FRAME



**460 VOLTS • 3-PHASE
FOOT MOUNT & C-FACE
3/4 TO 100 HP**

FOOT MOUNT (cont'd)

HP	SYN RPM	Frame	FL Nom Eff (%)	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	List Price	Mult Sym	
50	3600	365US	94.1	1.15	460	CCF2P50US64	LM21092	AH	980	\$7686	LU-1	
	3600	365U	94.1	1.15	460	CCF2P50U64	LM21799	AH	980	7686	LU-1	
	1800	365U	94.5	1.15	460	CCF4P50U64	LM19530	AH	1063	9146	LU-1	
	1800	365US	94.5	1.15	460	CCF4P50US64	LM21815	AH	1063	9146	LU-1	
	1800	365U	93.0	1.00	460	CCF4G50U64	LM23744	AQ	1063	8186	LU-1	
	1200	405U	94.1	1.15	460	CCF6P50U64	LM19533	AH	1110	11760	LU-1	
	1200	405US	94.1	1.15	460	CCF6P50US64	LM21819	AH	1110	11760	LU-1	
	1200	405U	92.6	1.00	460	CCF6G50U64	LM23748	AQ	1110	9399	LU-1	
	60	3600	405US	94.1	1.15	460	CCF2P60US64	LM19532	AH	1130	9144	LU-1
		3600	405U	94.1	1.15	460	CCF2P60U64	LM21800	AH	1130	9144	LU-1
1800		405U	95.0	1.15	460	CCF4P60U64	LM21391	AH	1110	11354	LU-1	
1800		405US	95.0	1.15	460	CCF4P60US64	LM21818	AH	1110	11354	LU-1	
1800		405U	93.5	1.00	460	CCF4G60U64	LM23747	AQ	1110	9076	LU-1	
1200		444U	94.1	1.15	460	CCF6P60U64	LM21393	AH	1787	13807	LU-1	
1200		444US	94.1	1.15	460	CCF6P60US64	LM21822	AH	1787	13808	LU-1	
1200		444U	92.6	1.00	460	CCF6G60U64	LM23750	AQ	1787	11036	LU-1	
75		3600	444US	94.1	1.15	460	CCF2P75US64	LM21093	AH	1685	12016	LU-1
		3600	444U	94.1	1.15	460	CCF2P75U64	LM21801	AH	1685	12015	LU-1
	1800	444U	95.0	1.15	460	CCF4P75U64	LM21392	AH	1787	14004	LU-1	
	1800	444US	95.0	1.15	460	CCF4P75US64	LM21821	AH	1787	14004	LU-1	
	1800	444U	93.5	1.00	460	CCF4G75U64	LM23749	AQ	1787	11796	LU-1	
	1200	445U	95.0	1.15	460	CCF6P75U64	LM19535	AH	1787	16371	LU-1	
	1200	445US	95.0	1.15	460	CCF6P75US64	LM21824	AH	1787	16373	LU-1	
	1200	445U	93.5	1.00	460	CCF6G75U64	LM23752	AQ	1787	13086	LU-1	
	100	3600	445US	95.4	1.15	460	CCF2P100US64	LM21094	AH	1685	15879	LU-1
		3600	445U	95.4	1.15	460	CCF2P100U64	LM21802	AH	1685	15879	LU-1
1800		445U	95.4	1.15	460	CCF4P100U64	LM19534	AH	1787	17409	LU-1	
1800		445US	95.4	1.15	460	CCF4P100US64	LM21823	AH	1787	17409	LU-1	
1800		445U	93.9	1.00	460	CCF4G100U64	LM23751	AQ	1787	14152	LU-1	

C-FACE WITH FEET

HP	SYN RPM	Frame	FL Nom Eff (%)	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	List Price	Mult Sym
3/4	1200	182C	82.5	1.15	460	CCN6P0.75UC64	LM21828	AH	120	\$990	LU-1
	1200	182C	81.0	1.00	460	CCN6G0.75UC64	LM23769	AQ	108	782	LU-1
1	1800	182C	87.5	1.15	460	CCN4P1UC64	LM21827	AH	120	935	LU-1
	1800	182C	86.0	1.00	460	CCN4G1UC64	LM23768	AQ	108	741	LU-1
	1200	184C	86.5	1.15	460	CCN6P1UC64	LM21835	AH	120	1127	LU-1
	1200	184C	85.0	1.00	460	CCN6G1UC64	LM23773	AQ	108	890	LU-1
1 1/2	3600	182C	85.5	1.15	460	CCN2P1.5UC64	LM21826	AH	120	864	LU-1
	1800	184C	88.5	1.15	460	CCN4P1.5UC64	LM21833	AH	120	996	LU-1
	1800	184C	87.0	1.00	460	CCN4G1.5UC64	LM23771	AQ	108	788	LU-1
	1200	184C	87.5	1.15	460	CCN6P1.5UC64	LM21834	AH	120	1239	LU-1
	1200	184C	86.0	1.00	460	CCN6G1.5UC64	LM23772	AQ	108	977	LU-1
2	3600	184C	85.5	1.15	460	CCF2P2UC64	LM21831	AH	132	950	LU-1
	1800	184C	89.5	1.15	460	CCF4P2UC64	LM21832	AH	132	1047	LU-1
	1800	184C	88.0	1.00	460	CCF4G2UC64	LM23770	AQ	170	826	LU-1
	1200	213C	87.5	1.15	460	CCF6P2UC64	LM21838	AH	181	1375	LU-1
	1200	213C	86.0	1.00	460	CCF6G2UC64	LM23775	AQ	170	1175	LU-1
3	3600	184C	87.5	1.15	460	CCF2P3UC64	LM21829	AH	132	1135	LU-1
	1800	213C	88.5	1.15	460	CCF4P3UC64	LM21837	AH	181	1204	LU-1
	1800	213C	87.0	1.00	460	CCF4G3UC64	LM23774	AQ	170	1021	LU-1
	1200	215C	89.5	1.15	460	CCF6P3UC64	LM21841	AH	181	1686	LU-1
	1200	215C	88.0	1.00	460	CCF6G3UC64	LM23778	AQ	170	1327	LU-1

Prices and data subject to change without notice.

Product numbers in red are STOCK items.



TOTALLY ENCLOSED AUTOMOTIVE DUTY • U-FRAME

460 VOLTS • 3-PHASE
FOOT MOUNT & C-FACE
3/4 TO 100 HP

C-FACE WITH FEET (cont'd)

HP	SYN RPM	Frame	FL Nom Eff (%)	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	List Price	Mult Sym
5	3600	213C	87.5	1.15	460	CCF2P5UC64	LM21836	AH	181	\$1268	LU-1
	1800	215C	89.5	1.15	460	CCF4P5UC64	LM21840	AH	181	1574	LU-1
	1800	215C	88.0	1.00	460	CCF4G5UC64	LM23776	AQ	170	1307	LU-1
	1200	254UC	90.2	1.15	460	CCF6P5UC64	LM21844	AH	272	2339	LU-1
	1200	254UC	88.7	1.00	460	CCF6G5UC64	LM23780	AQ	260	2088	LU-1
7 1/2	3600	215C	88.5	1.15	460	CCF2P7.5UC64	LM21839	AH	181	1526	LU-1
	1800	254UC	91.7	1.15	460	CCF4P7.5UC64	LM21843	AH	272	2069	LU-1
	1800	254UC	90.2	1.00	460	CCF4G7.5UC64	LM23779	AQ	260	1671	LU-1
	1200	256UC	91.0	1.15	460	CCF6P7.5UC64	LM21847	AH	344	2965	LU-1
	1200	256UC	89.5	1.00	460	CCF6G7.5UC64	LM23800	AQ	260	2389	LU-1
10	3600	254UC	89.5	1.15	460	CCF2P10UC64	LM21842	AH	272	1835	LU-1
	1800	256UC	91.7	1.15	460	CCF4P10UC64	LM21846	AH	272	2491	LU-1
	1800	256UC	90.2	1.00	460	CCF4G10UC64	LM23799	AQ	260	2011	LU-1
	1200	284UC	91.0	1.15	460	CCF6P10UC64	LM21849	AH	531	3682	LU-1
	1200	284UC	89.5	1.00	460	CCF6G10UC64	LM23802	AQ	525	2977	LU-1
15	3600	256UC	91.7	1.15	460	CCF2P15UC64	LM21845	AH	272	2312	LU-1
	1800	284UC	92.4	1.15	460	CCF4P15UC64	LM21848	AH	531	3458	LU-1
	1800	284UC	90.9	1.00	460	CCF4G15UC64	LM23801	AQ	525	2798	LU-1
	1200	324UC	92.4	1.15	460	CCF6P15UC64	LM21854	AH	757	5011	LU-1
	1200	324USC	92.4	1.15	460	CCF6P15USC64	LM21879	AH	757	5011	LU-1
	1200	324UC	90.9	1.00	460	CCF6G15UC64	LM23805	AQ	750	4059	LU-1
	1200	326UC	90.9	1.00	460	CCF6G20UC64	LM23807	AQ	750	4899	LU-1
20	3600	286UC	90.2	1.15	460	CCF2P20UC64	LM21850	AH	531	3181	LU-1
	1800	286UC	93.0	1.15	460	CCF4P20UC64	LM21851	AH	531	4209	LU-1
	1800	286UC	91.5	1.00	460	CCF4G20UC64	LM23803	AQ	525	3397	LU-1
	1200	326UC	92.4	1.15	460	CCF6P20UC64	LM21857	AH	757	6062	LU-1
	1200	326USC	92.4	1.15	460	CCF6P20USC64	LM21882	AH	757	6062	LU-1
	1200	326UC	90.9	1.00	460	CCF6G20UC64	LM23807	AQ	750	4899	LU-1
	1200	326UC	90.9	1.00	460	CCF6G20UC64	LM23807	AQ	750	4899	LU-1
25	3600	324USC	93.6	1.15	460	CCF2P25USC64	LM21893	AH	755	4147	LU-1
	3600	324UC	93.6	1.15	460	CCF2P25UC64	LM21852	AH	755	4760	LU-1
	1800	324UC	94.1	1.15	460	CCF4P25UC64	LM21853	AH	755	5336	LU-1
	1800	324USC	94.1	1.15	460	CCF4P25USC64	LM21878	AH	755	5337	LU-1
	1800	324UC	92.6	1.00	460	CCF4G25UC64	LM23804	AQ	748	4402	LU-1
	1200	364UC	93.0	1.15	460	CCF6P25UC64	LM21860	AH	1169	7427	LU-1
	1200	364USC	93.0	1.15	460	CCF6P25USC64	LM21885	AH	1169	7428	LU-1
30	1200	364UC	91.5	1.00	460	CCF6G25UC64	LM23809	AQ	1160	6027	LU-1
	3600	326USC	91.0	1.15	460	CCF2P30USC64	LM21880	AH	755	4942	LU-1
	3600	326UC	91.0	1.15	460	CCF2P30UC64	LM21855	AH	755	4942	LU-1
	1800	326UC	94.1	1.15	460	CCF4P30UC64	LM21856	AH	755	6186	LU-1
	1800	326USC	94.1	1.15	460	CCF4P30USC64	LM21881	AH	755	6186	LU-1
	1800	326UC	92.6	1.00	460	CCF4G30UC64	LM23806	AQ	748	5001	LU-1
	1200	365UC	93.0	1.15	460	CCF6P30UC64	LM21863	AH	1169	8347	LU-1
40	1200	365USC	93.0	1.15	460	CCF6P30USC64	LM21888	AH	1169	8347	LU-1
	1200	365UC	91.5	1.00	460	CCF6G30UC64	LM23811	AQ	1160	6762	LU-1
	3600	364USC	93.6	1.15	460	CCF2P40USC64	LM21883	AH	917	6536	LU-1
	3600	364UC	93.6	1.15	460	CCF2P40UC64	LM21858	AH	917	6535	LU-1
	1800	364UC	94.1	1.15	460	CCF4P40UC64	LM21859	AH	986	8239	LU-1
	1800	364USC	94.1	1.15	460	CCF4P40USC64	LM21884	AH	986	8239	LU-1
	1800	364UC	92.6	1.00	460	CCF4G40UC64	LM23808	AQ	977	6676	LU-1
1200	404UC	93.6	1.15	460	CCF6P40UC64	LM21864	AH	1123	10710	LU-1	
	404USC	93.6	1.15	460	CCF6P40USC64	LM21889	AH	1123	10709	LU-1	
	404UC	92.1	1.00	460	CCF6G40UC64	LM23812	AQ	1110	8663	LU-1	

Prices and data subject to change without notice.

Product numbers in red are STOCK items.

TOTALLY ENCLOSED AUTOMOTIVE DUTY • U-FRAME



460 VOLTS • 3-PHASE
FOOT MOUNT & C-FACE
3/4 TO 100 HP

C-FACE WITH FEET (cont'd)

HP	SYN RPM	Frame	FL Nom Eff (%)	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	List Price	Mult Sym
50	3600	365USC	94.1	1.15	460	CCF2P50USC64	LM21886	AH	989	\$8130	LU-1
	3600	365UC	94.1	1.15	460	CCF2P50UC64	LM21861	AH	989	8130	LU-1
	1800	365UC	94.5	1.15	460	CCF4P50UC64	LM21862	AH	1072	9590	LU-1
	1800	365USC	94.5	1.15	460	CCF4P50USC64	LM21887	AH	1072	9589	LU-1
	1800	365UC	93.0	1.00	460	CCF4G50UC64	LM23810	AQ	1063	7753	LU-1
	1200	405UC	94.1	1.15	460	CCF6P50UC64	LM21867	AH	1123	12287	LU-1
	1200	405USC	94.1	1.15	460	CCF6P50USC64	LM21892	AH	1123	12287	LU-1
	1200	405UC	92.6	1.00	460	CCF6G50UC64	LM23814	AQ	1110	9927	LU-1
60	3600	405USC	94.1	1.15	460	CCF2P60USC64	LM21890	AH	1143	9670	LU-1
	3600	405UC	94.1	1.15	460	CCF2P60UC64	LM21865	AH	1143	9670	LU-1
	1800	405UC	95.0	1.15	460	CCF4P60UC64	LM21866	AH	1123	11882	LU-1
	1800	405USC	95.0	1.15	460	CCF4P60USC64	LM21891	AH	1123	11882	LU-1
	1800	405UC	93.5	1.00	460	CCF4G60UC64	LM23813	AQ	1110	9603	LU-1
	1200	444UC	94.1	1.15	460	CCF6P60UC64	LM21870	AH	1810	14460	LU-1
	1200	444USC	94.1	1.15	460	CCF6P60USC64	LM21895	AH	1810	14461	LU-1
	1200	444UC	92.6	1.00	460	CCF6G60UC64	LM23816	AQ	1787	11689	LU-1
75	3600	444USC	94.1	1.15	460	CCF2P75USC64	LM21877	AH	1708	12669	LU-1
	3600	444UC	94.1	1.15	460	CCF2P75UC64	LM21868	AH	1708	12668	LU-1
	1800	444UC	95.0	1.15	460	CCF4P75UC64	LM21869	AH	1810	14657	LU-1
	1800	444USC	95.0	1.15	460	CCF4P75USC64	LM21894	AH	1810	14657	LU-1
	1800	444UC	93.5	1.00	460	CCF4G75UC64	LM23815	AQ	1787	11848	LU-1
	1200	445UC	95.0	1.15	460	CCF6P75UC64	LM21873	AH	1810	17025	LU-1
	1200	445USC	95.0	1.15	460	CCF6P75USC64	LM21898	AH	1810	17025	LU-1
	1200	445UC	93.5	1.00	460	CCF6G75UC64	LM23818	AQ	1787	13739	LU-1
100	3600	445USC	95.4	1.15	460	CCF2P100USC64	LM21896	AH	1708	16532	LU-1
	3600	445UC	95.4	1.15	460	CCF2P100UC64	LM21871	AH	1708	16532	LU-1
	1800	445UC	95.4	1.15	460	CCF4P100UC64	LM21872	AH	1810	18060	LU-1
	1800	445USC	95.4	1.15	460	CCF4P100USC64	LM21897	AH	1810	18060	LU-1
	1800	445UC	93.9	1.00	460	CCF4G100UC64	LM23817	AQ	1787	14805	LU-1

C-FACE FOOTLESS

HP	SYN RPM	Frame	FL Nom Eff (%)	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	List Price	Mult Sym
3/4	1200	182C	82.5	1.15	460	CCN6P0.75UCN64	TBD	AH	120	\$990	LU-1
1	1800	182C	87.5	1.15	460	CCN4P1UCN64	LM23781	AH	120	935	LU-1
	1200	184C	86.5	1.15	460	CCN6P1UCN64	LM24037	AH	120	1127	LU-1
1 1/2	3600	182C	85.5	1.15	460	CCN2P1.5UCN64	TBD	AH	120	865	LU-1
	1800	184C	88.5	1.15	460	CCN4P1.5UCN64	LM23783	AH	120	996	LU-1
	1200	184C	87.5	1.15	460	CCN6P1.5UCN64	TBD	AH	120	1239	LU-1
2	3600	184C	85.5	1.15	460	CCF2P2UCN64	LM25496	AH	132	950	LU-1
	1800	184C	89.5	1.15	460	CCF4P2UCN64	LM23782	AH	132	1047	LU-1
	1200	213C	87.5	1.15	460	CCF6P2UCN64	TBD	AH	181	1376	LU-1
3	3600	184C	87.5	1.15	460	CCF2P3UCN64	TBD	AH	132	1068	LU-1
	1800	213C	88.5	1.15	460	CCF4P3UCN64	LM23854	AH	181	1384	LU-1
	1200	215C	89.5	1.15	460	CCF6P3UCN64	LM25667	AH	181	1686	LU-1
5	3600	213C	87.5	1.15	460	CCF2P5UCN64	LM25203	AH	181	1268	LU-1
	1800	215C	89.5	1.15	460	CCF4P5UCN64	LM24072	AH	181	1717	LU-1
	1200	254UC	90.2	1.15	460	CCF6P5UCN64	TBD	AH	272	2339	LU-1
7 1/2	3600	215C	88.5	1.15	460	CCF2P7.5UCN64	TBD	AH	181	1439	LU-1
	1800	254UC	91.7	1.15	460	CCF4P7.5UCN64	LM23784	AH	272	2069	LU-1
	1200	256UC	91.0	1.15	460	CCF6P7.5UCN64	TBD	AH	344	2965	LU-1

Prices and data subject to change without notice.

Product numbers in red are STOCK items.



TOTALLY ENCLOSED AUTOMOTIVE DUTY • U-FRAME

460 VOLTS • 3-PHASE
FOOT MOUNT & C-FACE
3/4 TO 100 HP

C-FACE FOOTLESS (cont'd)

HP	SYN RPM	Frame	FL Nom Eff (%)	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	List Price	Mult Sym
10	3600	254UC	89.5	1.15	460	CCF2P10UCN64	TBD	AH	272	\$1836	LU-1
	1800	256UC	91.7	1.15	460	CCF4P10UCN64	LM23855	AH	272	2491	LU-1
	1200	284UC	91.0	1.15	460	CCF6P10UCN64	TBD	AH	531	3682	LU-1
15	3600	256UC	91.7	1.15	460	CCF2P15UCN64	TBD	AH	272	2311	LU-1
	1800	284UC	92.4	1.15	460	CCF4P15UCN64	LM23856	AH	531	3458	LU-1
	1200	324UC	92.4	1.15	460	CCF6P15UCN64	TBD	AH	757	5011	LU-1
20	3600	286UC	90.2	1.15	460	CCF2P20UCN64	TBD	AH	531	3180	LU-1
	1800	286UC	93.0	1.15	460	CCF4P20UCN64	LM23857	AH	531	4209	LU-1
	1200	326UC	92.4	1.15	460	CCF6P20UCN64	TBD	AH	757	6062	LU-1
25	3600	324USC	93.6	1.15	460	CCF2P25USCN64	TBD	AH	755	4145	LU-1
	1800	324UC	94.1	1.15	460	CCF4P25UCN64	LM23858	AH	755	5336	LU-1
	1200	364UC	93.0	1.15	460	CCF6P25UCN64	TBD	AH	1169	7428	LU-1
30	3600	326USC	91.0	1.15	460	CCF2P30USCN64	TBD	AH	755	4942	LU-1
	1800	326UC	94.1	1.15	460	CCF4P30UCN64	LM23862	AH	755	6187	LU-1
	1200	365UC	93.0	1.15	460	CCF6P30UCN64	TBD	AH	1169	8348	LU-1
40	3600	364USC	93.6	1.15	460	CCF2P40USCN64	TBD	AH	917	6533	LU-1
	1800	364UC	94.1	1.15	460	CCF4P40UCN64	LM23859	AH	986	8239	LU-1
	1200	404UC	93.6	1.15	460	CCF6P40UCN64	TBD	AH	1123	10710	LU-1
50	3600	365USC	94.1	1.15	460	CCF2P50USCN64	TBD	AH	989	8130	LU-1
	1800	365UC	94.5	1.15	460	CCF4P50UCN64	LM23861	AH	1072	9590	LU-1
	1200	405UC	94.1	1.15	460	CCF6P50UCN64	TBD	AH	1123	12288	LU-1
60	3600	405USC	94.1	1.15	460	CCF2P60USCN64	TBD	AH	1143	9670	LU-1
	1800	405UC	95.0	1.15	460	CCF4P60UCN64	LM23860	AH	1123	11882	LU-1
	1200	444UC	94.1	1.15	460	CCF6P60UCN64	TBD	AH	1810	14461	LU-1
75	3600	444USC	94.1	1.15	460	CCF2P75USCN64	TBD	AH	1708	12667	LU-1
	1800	444UC	95.0	1.15	460	CCF4P75UCN64	LM24315	AH	1810	14657	LU-1
	1200	445UC	95.0	1.15	460	CCF6P75UCN64	TBD	AH	1810	17025	LU-1
100	3600	445USC	95.4	1.15	460	CCF2P100USCN64	TBD	AH	1708	16532	LU-1
	1800	445UC	95.4	1.15	460	CCF4P100UCN64	TBD	AH	1810	18061	LU-1

Prices and data subject to change without notice.

Product numbers in red are STOCK items.