



THREE PHASE • TEFC • RIGID BASE

HP	SYN RPM 60 Hz	NEMA Frame	Brake Rating (ft-lbs)	Catalog Number	App. Wgt. (lbs.)	Voltage	F.L. Amps 230V	% F.L. Eff.	"C" Dim. (Inches)
1/3	1800	56	3	114151.00● A	28	208-230/460	1.3	72.0	13.56
1/2	1800	56	3	114150.00● A	33	208-230/460	1.8	78.5	14.06
	1200	56	6	114149.00 A	33	208-230/460	2.4	70.0	15.56
3/4	1800	56	6	114147.00	34	208-230/460	2.8	77.0	15.56
	1200	56	6	114148.00 A	43	208-230/460	3.0	75.5	16.06
1	1800	56	6	114146.00	37	208-230/460	3.8	77.0	16.06
	1800	143T	6	G121679.00	40	208-230/460	3.1	82.5	17.50
	1200	145T	10	G121050.00	45	208-230/460	3.6	80.0	17.52
1½	1800	56	10	116767.00 A	44	208-230/460	4.4	84.0	17.08
	1800	145T	10	G120329.00	44	208-230/460	4.4	84.0	17.52
2	1800	145T	10	G120330.00	53	208-230/460	5.6	84.0	18.00
	1200	184T	15	G131620.00	80	208-230/460	7.2	86.5	20.33
3	1800	182T	15	G131613.00	78	230/460	8.2	87.5	18.83
	1200	213T	35	G140601.00	147	208-230/460	12.0	87.5	26.49
5	1800	184T	25	G131614.00	102	230/460	13.0	87.5	20.78
7½	1800	213T	35	G140603.00	162	208-230/460	20.4	89.5	26.49
10	1800	215T	50	G140636.00	174	208-230/460	26.0	89.5	27.99

THREE PHASE • TEFC • C FACE WITH BASE

HP	SYN RPM 60 Hz	NEMA Frame	Brake Rating (ft-lbs)	Catalog Number	App. Wgt. (lbs.)	Voltage	F.L. Amps 230V	% F.L. Eff.	"C" Dim. (Inches)
1/3	1800	56C	3	110669.00●	30	208-230/460	1.3	72.0	13.56
1/2	1800	56C	3	110670.00●†	34	208-230/460	1.8	78.5	14.06
		56C	3	114154.00	34	208-230/460	2.4	74.0	15.06
	1200	56C	3	114152.00	34	208-230/460	2.4	70.0	15.56
3/4	1800	56C	6	110671.00●†	34	208-230/460	2.5	80.0	14.56
	1800	56C	6	114155.00	46	208-230/460	2.8	77.0	15.56
1	1800	56C	6	110679.00	32	208-230/460	3.6	77.0	15.56
	1800	143TC	6	G121557.00	43	208-230/460	3.1	82.5	17.50
1½	1800	145TC	10	G121051.00	45	230/460	4.4	84.0	17.50
2	1800	145TC	10	G121052.00	59	208-230/460	5.6	84.0	18.00
3	1800	182TC	15	G131617.00	79	230/460	8.2	87.5	18.83
5	1800	184TC	25	G131618.00	117	230/460	13.0	87.5	20.78
7½	1800	213TC	35	G140605.00	163	208-230/460	20.4	89.5	26.49
10	1800	215TC	50	G140639.00	175	208-230/460	26.0	89.5	27.99



THREE PHASE • TEFC • C FACE LESS BASE

HP	SYN RPM 60 Hz	NEMA Frame	Brake Rating (ft-lbs)	Catalog Number	App. Wgt. (lbs.)	Voltage	F.L. Amps 230V	% F.L. Eff.	"C" Dim. (Inches)
1/3	1800	56C	3	114158.00●	26	208-230/460	1.3	72.0	13.56
1/2	1800	56C	3	114159.00	26	208-230/460	2.0	74.0	15.06
3/4	1800	56C	6	114160.00	34	208-230/460	2.8	77.0	15.06
1	1800	56C	6	114161.00	31	208-230/460	3.6	77.0	15.56
	1800	143TC	6	121556.00	37	208-230/460	3.8	77.0	17.00
1½	1800	56C	10	116768.00	40	208-230/460	5.0	78.5	16.56
	1800	145TC	10	120331.00	40	208-230/460	5.0	78.5	17.00
2	1800	145TC	10	120332.00	51	208-230/460	6.0	84.0	18.00
3	1800	182TC	15	131610.00	69	230/460	9.0	84.0	18.73
5	1800	184TC	25	131611.00	92	230/460	13.2	86.0	19.18
7½	1800	S213TC	35	131612.00	149	230/460	19.6	87.0	25.29
10	1800	215TC	50	140637.00 A	136	208-230/460	26.0	89.5	27.99

- These motors are totally enclosed, non-ventilated.
- † Class F insulated.
- A Subject to Availability.

All 180 and 210 frame Rolled Steel motors have Class F Insulation.

Catalog numbers in green are EPACT motors.

WASHGUARD • TENV/TEFC • C FACE WITH BASE

HP	SYN RPM 60 Hz	NEMA Frame	Brake Rating (ft-lbs)	Catalog Number	App. Wgt. (lbs.)	Voltage	F.L. Amps 230V	% F.L. Eff.	"C" Dim. (Inches)
1/3	1800	56C	3	116466.00●	40	208-230/460	1.3	72.0	14.00
1/2	1800	56C	3	116467.00●	42	208-230/460	1.8	78.5	14.50
3/4	1800	56C	6	116468.00●	44	208-230/460	2.5	80.0	15.00
1	1800	56C	6	116469.00●	48	208-230/460	3.2	80.0	15.50
	1800	143TC	6	121616.00●	49	208-230/460	3.2	80.0	16.06
1½	1800	145TC	10	G121617.00	50	208-230/460	4.4	84.0	19.01
2	1800	145TC	10	G121618.00	62	208-230/460	5.6	84.0	19.01

WASHGUARD • TENV/TEFC • C FACE LESS BASE

HP	SYN RPM 60 Hz	NEMA Frame	Brake Rating (ft-lbs)	Catalog Number	App. Wgt. (lbs.)	Voltage	F.L. Amps 230V	% F.L. Eff.	"C" Dim. (Inches)
1/3	1800	56C	3	116462.00●	39	208-230/460	1.3	72.0	14.00
1/2	1800	56C	3	116463.00●	41	208-230/460	1.8	78.5	14.50
3/4	1800	56C	6	116464.00●	43	208-230/460	2.5	80.0	15.00
1	1800	56C	6	116465.00●	45	208-230/460	3.2	80.0	15.50
	1800	143TC	6	121613.00●	46	208-230/460	3.2	80.0	15.56
1½	1800	145TC	10	121614.00	49	208-230/460	5.0	78.5	18.01
2	1800	145TC	10	121615.00	61	208-230/460	6.2	81.5	18.51

ALL-STAINLESS • TENV • C FACE WITH BASE

HP	SYN RPM 60 Hz	NEMA Frame	Brake Rating (ft-lbs)	Catalog Number	App. Wgt. (lbs.)	Voltage	F.L. Amps 230V	% F.L. Eff.	"C" Dim. (Inches)
1/2	1800	56C	3	116483.00●	59	208-230/460	1.6	78.5	15.85
1	1800	56C	6	116484.00●	69	208-230/460	3.0	81.5	15.85

- These motors are totally enclosed, non-ventilated.