



PREMIUM STAINLESS STEEL DUCK



IEC ALL-STAINLESS PREMIUM MOTORS

IEC B5 FLANGE - ROUND BODY

HP/ KW	SYN RPM	Frame	Catalog Number	App. Wgt. (lbs.)	Volts DC	F.L. Amps DC	% FL Eff.	"C" Dim. (Inches)
1/3-0.25	1800	71	103403.00●	30	208-230/460	1.3	70.5	9.87
	1800	80	103405.00●	30	208-230/460	1.3	70.5	9.87
1/2-0.37	1800	71	103404.00●	32	208-230/460	1.6	76.0	11.62
	1800	80	103406.00●	32	208-230/460	1.6	76.0	11.62
3/4-0.55	1800	80	103407.00	38	208-230/460	2.3	77.0	12.26
1- 0.75	1800	90	117516.00	45	208-230/460	3.1	82.5	13.13
1.5 - 1.1	1800	90	117517.00	49	208-230/460	4.4	84.0	13.63
2 - 1.5	1800	90	117518.00	49	208-230/460	5.6	84.0	13.63

IEC B5 FLANGE - RIGID BASE

HP/ KW	SYN RPM	Frame	Catalog Number	App. Wgt. (lbs.)	Volts DC	F.L. Amps DC	% FL Eff.	"C" Dim. (Inches)
1/3-0.25	1800	80	103408.00●	30	208-230/460	1.3	70.5	9.50
1/2-0.37	1800	80	103409.00●	32	208-230/460	1.6	76	12.75
3/4-0.55	1800	80	103410.00	38	208-230/460	2.3	77	12.26

IEC B14 FLANGE - ROUND BODY

HP/ KW	SYN RPM	Frame	Catalog Number	App. Wgt. (lbs.)	Volts DC	F.L. Amps DC	% FL Eff.	"C" Dim. (Inches)
1/3-0.25	1800	71	103395.00●	30	208-230/460	1.3	70.5	9.83
	1800	80	103397.00●	30	208-230/460	1.3	70.5	9.72
1/2-0.37	1800	71	103396.00●	32	208-230/460	1.6	76	11.58
	1800	80	103398.00●	32	208-230/460	1.6	76	11.582
3/4-0.55	1800	80	103399.00	38	208-230/460	2.3	77	12.48

IEC B14 FLANGE - RIGID BASE

HP/ KW	SYN RPM	Frame	Catalog Number	App. Wgt. (lbs.)	Volts DC	F.L. Amps DC	% FL Eff.	"C" Dim. (Inches)
1/3-0.25	1800	80	103400.00●	31	208-230/460	1.3	70.5	9.72
1/2-0.37	1800	80	103401.00●	33	208-230/460	1.6	76	11.58
3/4-0.55	1800	80	103402.00	39	208-230/460	2.3	77	12.48