



ADJUSTABLE MOTOR BASES—NEMA 48-447T FRAMES

Heavy gauge steel mounting bases simplify the installation of motors and make the tensioning, maintenance and replacement of belts a simple efficient task. Fabricated from sheet or steel plate, then primed and finished in a gray rust and corrosion resistant oven-baked finish. Gussets and

reinforcing channels on larger units and continuous seam welding on all units give these bases strength and durability for a long life. A single (215T frame and smaller) or double (NEMA 254T frame and larger) zinc plated adjusting screw is provided. Motor mounting bolts are included.



NEMA 48 thru 215T



NEMA 254T thru 447T

Frame	Catalog Number	List Price	Disc. Sym.	AL	AM	AX	BB	E	F	AO	AR	AU**	BT	AT	XC	D* Bolt	AY Bolt	App. Wgt. (lbs.)
48	175032	\$ 64	A	10	6 1/4	1 1/8	4 1/4	2 1/8	1 3/8	3 1/2	2 3/4	3/8	3	.078	7/8	5/16 x 1	3/8 x 4	2
56	175033	64	A	10 5/8	6 1/2	1 1/8	4 1/2	2 7/16	1 1/2	3 13/16	2 7/8	3/8	3	.078	7/8	5/16 x 1	3/8 x 4	3
143T	175034	75	B	10 1/2	7 1/2	1 1/8	5 1/2	2 3/4	2	3 3/4	3 3/8	3/8	3	.119	1 3/16	5/15 x 1	3/8 x 4	5
145T	175035	75	B	10 1/2	8 1/2	1 1/8	6 1/2	2 3/4	2 1/2	3 3/4	3 7/8	3/8	3	.119	1 3/16	5/15 x 1	3/8 x 4	6
182T	175036	97	B	12 3/4	9 1/2	1 1/2	6 1/2	3 3/4	2 1/4	4 1/2	4 1/4	1/2	3	.134	1 1/2	3/8 x 1 3/4	1/2 x 5	9
184T	175037	97	B	12 3/4	10 1/2	1 1/2	7 1/2	3 3/4	2 3/4	4 1/2	4 3/4	1/2	3	.134	1 1/2	3/8 x 1 3/4	1/2 x 5	9
213T	175038	120	C	15	11	1 3/4	7 1/2	4 1/4	2 3/4	5 1/4	4 3/4	1/2	3 1/2	.164	1 1/2	3/8 x 1 3/4	1/2 x 5	13
215T	175039	120	C	15	12 1/2	1 3/4	9	4 1/4	3 1/2	5 1/4	5 1/2	1/2	3 1/2	.164	1 1/2	3/8 x 1 3/4	1/2 x 5	15
254T	175040	184	C	17 3/4	15 1/8	2	10 3/4	5	4 1/8	6 1/4	6 5/8	5/8	4	3/16	1 7/16	1/2 x 1 3/4	5/8 x 6	17
256T	175041	184	C	17 3/4	16 7/8	2	12 1/2	5	5	6 1/4	7 1/2	5/8	4	3/16	1 7/16	1/2 x 1 3/4	5/8 x 6	18
284T	175042	200	C	19 3/4	16 7/8	2	12 1/2	5 1/2	4 3/4	7	7 1/2	5/8	4 1/2	3/16	1 11/16	1/2 x 2	5/8 x 6	21
286T	175043	200	C	19 3/4	18 3/8	2	14	5 1/2	5 1/2	7	8 1/4	5/8	4 1/2	3/16	1 11/16	1/2 x 2	5/8 x 6	22
324T	175044	265	C	22 3/4	19 1/4	2 1/2	14	6 1/4	5 1/4	8	8 1/2	3/4	5 1/4	3/16	2 3/16	5/8 x 2 1/2	3/4 x 9	31
326T	175045	265	C	22 3/4	20 3/4	2 1/2	15 1/2	6 1/4	6	8	9 1/4	3/4	5 1/4	3/16	2 3/16	5/8 x 2 1/2	3/4 x 9	32
364T	175046	349	C	25 1/2	20 1/2	2 1/2	15 1/2	7	5 5/8	9	9 1/8	3/4	6	1/4	2 1/16	5/8 x 2 1/2	3/4 x 9	44
365T	175047	349	C	25 1/2	21 1/2	2 1/2	16 1/2	7	6 1/8	9	9 5/8	3/4	6	1/4	2 1/16	5/8 x 2 1/2	3/4 x 9	45
404T	175048	628	C	28 3/4	22 3/8	3	16 1/2	8	6 1/8	10	9 7/8	7/8	7	1/4	2 1/2	3/4 x 3	3/4 x 11	60
405T	175049	628	C	28 3/4	23 7/8	3	18	8	6 7/8	10	10 5/8	7/8	7	1/4	2 1/2	3/4 x 3	3/4 x 11	61
444T	175088	777	C	31 1/4	24 5/8	3	19 1/4	9	7 1/4	11	11	7/8	7 1/2	1/4	2 1/2	3/4 x 3	3/4 x 11	68
445T	175089	777	C	31 1/4	26 5/8	3	21 1/4	9	8 1/4	11	12	7/8	7 1/2	1/4	2 1/2	3/4 x 3	3/4 x 11	73
447T	175090	858	C	31 1/4	30 1/8	3	24 3/4	9	10	11	13 3/4	7/8	7 1/2	5/16	3	3/4 x 3 1/2	3/4 x 11	92
449T	175302	858	C	31 1/4	35 1/8	3	29 3/4	9	12 1/2	11	16 1/4	7/8	7 1/2	5/16	3	3/4 x 3 1/2	3/4 x 11	95

\* Motor mounting bolt diameter and length, four supplied with each base.  
\*\* Base mounting bolts, four required—not supplied with base.

NOTE: These bases are not suitable for vertical mounting. All dimensions in inches.

TRANSITION BASES

Transition bases compensate for the difference in mounting dimensions and shaft height of a rigid base NEMA T frame to the next higher NEMA U frame. This makes it possible, for example, to replace a 10 HP NEMA 254U frame motor with a 10 HP NEMA 215T frame motor without modifying the basic installation. Made of the same high-quality materials and

construction as the adjustable motor bases above. They are for horizontal mountings, shimming may be needed for direct coupled loads. Thread size listed is for mounting transition base to the "T" frame motor. Dimensions listed are for one piece—two are supplied, one for each side of the motor's foot.



Converts T Frame	To U Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Height (Inches)	Width (Inches)	Length (Inches)	Thread
143T/145T	182/184	175091	\$ 65	B	2	1	2 1/4	7 1/2	5/16-18
182T/184T	213/215	175092	94	B	3	3/4	1 3/4	9 1/2	3/8-16
213T/215T	254U/256U	175093	109	C	5	1	2 7/16	12 3/4	3/8-16
254T/256T	284U/286U	175094	155	C	8	3/4	2 3/4	14 1/4	1/2-13
284T/286T	324U/326U	175095	206	C	10	1	3 1/4	15 3/4	1/2-13
324T/326T	364U/365U	175097	261	C	13	1	3 11/16	16 1/2	5/8-11
364T/365T	404U/405U	175098	349	C	22	1	4 1/4	18 5/8	5/8-11
404T/405T	444U/445U	175127	447	C	24	1	4 1/4	21 5/8	3/4-10

Motor Accessories