



AGRICULTURAL MOTORS

GENERAL PURPOSE • SINGLE PHASE

FARM DUTY • GENERAL PURPOSE

Heavy duty single phase Hi-Torque Motors designed specifically for severe "farm duty" applications.

Mechanical Features:

Gasketed capacitor housing and conduit boxes provide protection in all environments.
 Double sealed ball bearings prelubricated with Exxon POLYREX® EM grease having operating temperature range of -20°F to +350°F and special formulation to provide extra bearing protection.
 Rubber boot over manual protector reset button provides weather protection.

Electrical Features:

Low temperature manual overload protector protects against extreme overload.
 Class "F" copper windings and varnish.
 Capacitor start provides high starting torque with normal starting current.
All 180 and 210 frame Rolled Steel motors have Class F Insulation.



HIGH TORQUE • RIGID BASE SINGLE PHASE • TEFC

HP	RPM 60 Hz	NEMA Frame	Catalog Number	Disc. Sym.	App. Wgt. (lbs.)	Voltage	Over-load Prot.	F.L. Amps 230V	"C" Dim. (Inches)
1/3	1725	56	113256	A	20	115/208-230	Man.	3.2	10.81
1/2	1725	56	110086	A	22	115/208-230	Man.	4.4	10.81
3/4	1725	56	110087	A	26	115/208-230	Man.	5.4	11.31
1	1725	56	110088	A	30	115/208-230	Man.	7.0	11.81
	1725	143T	121569	A	30	115/208-230	Man.	7.0	12.75
1½	1725	56H	110089☆□	A	41	115/208-230	Man.	8.6	12.61
	56HZ/1725	145T	113938■	A	39	115/208-230	Man.	8.6	13.25
2	1725	56HZ/145T	110090☆■	A	43	230	Man.	9.2	13.75
	1740	182T	131541	B	50	115/208-230	Man.	12.4	14.46
3	1740	184T	131542	B	83	230	Man.	19.0	16.46
5	1740	184T	131543☆	B	96	230	Man.	20.5	17.46
7½	1740	215T	140707☆	B	144	230	Man.	32.0	20.21
10	1740	215T	140706☆	B	152	230	Man.	40.0	20.71

EXTRA HI-TORQUE RIGID BASE SINGLE PHASE • TEFC

Extra Hi-Torque rated 5, 7½ and 10 HP Motors deliver starting torque as high as 300-400% of motor's full load torque with all mechanical and electrical features listed above.



HP	RPM 60 Hz	NEMA Frame	Catalog Number	Disc. Sym.	App. Wgt. (lbs.)	Voltage	Over-load Prot.	F.L. Amps 230V	"C" Dim. (Inches)
2	1740	182T	131541	B	50	115/208-230	Man.	12.4	14.46
3	1740	184T	131542	B	83	230	Man.	19.0	16.46
5	1740	215T	140203	B	119	230	Man.	24.0	18.71
		215TZ	140223	B	150	230	Man.	24.0	18.71
7½	1740	215T	140130	B	144	230	Man.	33.6	20.21
		215TZ	140209	B	141	230	Man.	33.6	20.21
10	1740	215T	140414	B	156	230	Man.	40.0	20.71

HIGH TORQUE C FACE LESS BASE SINGLE PHASE • TEFC

NEMA C Face Motor designed with overspeed protection on mechanical centrifugal starting switch.



HIGH TORQUE C FACE WITH BASE SINGLE PHASE • TEFC

NEMA C Face Motor designed with overspeed protection on mechanical centrifugal starting switch.



HP	RPM 60 Hz	NEMA Frame	Catalog Number	Disc. Sym.	App. Wgt. (lbs.)	Voltage	Over-load Prot.	F.L. Amps 230V	"C" Dim. (Inches)
1/3	1725	56C	113290	A	28	115/208-230	Man.	3.2	10.81
1/2	1725	56C	110492	A	22	115/208-230	Man.	4.4	10.81
3/4	1725	56C	110493	A	29	115/208-230	Man.	5.4	11.31
1	1725	56C	110494	A	33	115/208-230	Man.	7.0	11.81
1½	1725	56C	110495☆	A	43	115/208-230	Man.	8.6	12.31
2	1725	145TC	120855†☆	B	45	230	Man.	9.2	13.75
3	1740	184TC	131603	B	104	230	Man.	19.0	16.47
5	1740	184TC	131602☆	B	104	230	Man.	20.5	17.47

HP	RPM 60 Hz	NEMA Frame	Catalog Number	Disc. Sym.	App. Wgt. (lbs.)	Voltage	Over-load Prot.	F.L. Amps 230V	"C" Dim. (Inches)
1/3	1725	56C	116485	A	29	115/208-230	Man.	3.2	10.81
1/2	1725	56C	116486	A	23	115/208-230	Man.	4.4	10.81
3/4	1725	56C	116487	A	30	115/208-230	Man.	5.4	11.31
1	1725	56C	116488	A	34	115/208-230	Man.	7.0	11.81
1½	1725	56HC	116489☆	A	44	115/208-230	Man.	8.6	12.81
2	1725	145TC	121625†☆	B	46	230	Man.	9.2	13.75
3	1740	184TC	131994	B	105	230	Man.	19.0	16.47
5	1740	184TC	131995☆	B	105	230	Man.	20.5	17.47

■ Combination 56 HZ base has mounting holes for NEMA 56 and 143-5T and a standard NEMA 145T frame shaft of 7/8" diameter.
 □ Combination 56H base has mounting holes for NEMA 56 and 143-5T and a standard NEMA 56 frame shaft.
 ☆ Capacitor start/capacitor run design for reduced amperage, others are capacitor start/induction run.
 † Class F insulated.
 ‡ These motors have a NEMA 215T base mounting pattern and shaft height of 5.25", with usable length of 3 3/8" and diameter of 1 1/8" with standard key.



AGRICULTURAL MOTORS

SINGLE AND THREE PHASE

AERATION FAN MOTORS BELT-DRIVEN • DUST-TIGHT

Totally enclosed air over motors, dust-tight, suitable for shaft-mounted fans or belt driven fans. Capacitor start designs. Designed to be used within the airflow of the driven fan, these motors offer protection from the environment and are finished in epoxy enamel to resist corrosion in tough atmospheres. Lubricated with high temperature Exxon POLYREX® EM lubricant. Grounding provisions. Fully gasketed. Single phase motors have built-in terminal panel for quick, easy connections.



SINGLE PHASE • CAPACITOR START • TEAO • RIGID BASE

HP	RPM 60 Hz	NEMA Frame	Catalog Number	Disc. Sym.	App. Wgt. (lbs.)	Voltage	Over- load Prot.	F.L. Amps 230V	"C" Dim. (Inches)
3/4	3450	56	111332 ^⑦	A	27	115/230	None	5.0	10.90
1	3450	56	111333 ^⑦	A	29	115/230	None	6.0	10.90
1½	3450	56	111949 ^⑦	A	32	115/230	None	8.5	11.40
		143TZ	120374 ^⑧	B	31	115/230	None	8.5	11.84
2	3450	145TZ	120375 ^⑧	B	41	230	None	10.0	13.34
3	3450	145T	120376 [☆]	B	45	230	None	12.8	13.84

CROP DRYER MOTORS

Open air over, fan-on-shaft design motors for crop drying applications. Designed for continuous duty operation. Class F insulation system. Thermostats provide thermal overload protection on all units. Extra nameplate included for remote mounting. Keyed shaft with 1/4-20 UNC tapped hole in end.



Capacitors supplied on single phase models. All models include sealed bearings, rodent screens, gray epoxy paint and 3/4" leads exiting the motor at 12 o'clock.

SINGLE PHASE

HP	RPM 60 Hz	NEMA Frame	Catalog Number	Disc. Sym.	App. Wgt. (lbs.)	Voltage	Over- load Prot.	F.L. Amps 230V	"C" Dim. (Inches)
5-7	3450	182TZ	131847	B	91	230	T-Stat	27.2-35.0	16.44
7.5-10	3450	182TZ	131848	B	95	230	T-Stat	31.0-42.0	16.44
10-15	3450	215TZ	140640	B	159	230	T-Stat	39.5-61.5	20.42

GRAIN STIRRING MOTORS DUST-TIGHT

Dust-Tight Motors designed to operate inside agricultural storage bins for stirring grain, corn and other agricultural products.



Mechanical Features:

External cast aluminum cooling fan at shaft end keeps grain from obstructing fan operation. Prelubricated double shielded ball bearings packed with Exxon POLYREX® EM grease (temperature range -20°F to +350°F). Totally enclosed construction with gasketed conduit box and capacitor cases. Moisture drain hole in endshield opposite shaft for vertical shaft up mounting. Rugged 205 bearing shaft-end. Shaft is 7/8" diameter, useable length of 15/16". "BA" dimension is 35/8".

Electrical Features:

Energy-saving, extra high torque designs.

SINGLE PHASE • RIGID BASE • TEFC

HP	RPM 60 Hz	NEMA Frame	Catalog Number	Disc. Sym.	App. Wgt. (lbs.)	Voltage	Over- load Prot.	F.L. Amps 230V	"C" Dim. (Inches)
1½	1725	56HZ	111330	A	42	115/208-230	Man.	8.6	12.31

^⑦ Standard 5/8" diameter shaft with keyway plus 3/4" deep hole drilled and tapped to 1/4-20 UNC in end of shaft to facilitate mounting of some fan blades.
^⑧ Standard 7/8" diameter shaft with keyway plus 3/4" deep hole drilled and tapped to 1/4-20 UNC in end of shaft to facilitate mounting of some fan blades.
[☆] Capacitor start/capacitor run design for reduced amperage, others are capacitor start/induction run.

All 180 and 210 frame Rolled Steel motors have Class F Insulation.

CATFISH POND MOTORS

Specially designed for aeration systems used on aquaculture ponds, these motors are designed for dependable outdoor applications. Typically C-face connected to a right-angle gearbox and installed on a floating aeration platform.



Hi-torque motors are epoxy-painted with a corrosion-resistant interior coating. Stainless hardware, fan guard, lifting lug, and conduit box cover for maximum protection against corrosion. Drain holes in the conduit box and in four positions on each end of the frame to purge condensate and moisture that may enter the motor. Ball bearings are double-sealed and lubricated with Exxon POLYREX[®] EM high temperature, moisture resistant lubricant.

All 180 and 210 frame Rolled Steel motors have Class F Insulation.

SINGLE AND THREE PHASE • C FACE WITH BASE • TEFC

HP	RPM 60 Hz	NEMA Frame	Catalog Number	Disc. Sym.	App. Wgt. (lbs.)	Voltage	Phase	F.L. Amps 460V	"C" Dim. (Inches)
10	1740	215TC	140705*	B	204	230	1	40.0	20.71
	1740	215TC	G140709	B	169	208-230/460	3	26.0	18.71

* Single phase motor has manual reset overload protection

MILK TRANSFER PUMP MOTOR

General Specifications:

Totally enclosed non-ventilated motor. Direct replacement for Surge milk pumps, Babson motor #27732.



Mechanical Features:

Special moisture resistant design with double sealed ball bearings. Bearings and bearing cavities packed with high temperature moisture resistant lubricant. Drain holes to expel moisture and water. Epoxy paint.

Electrical Features:

Permanent split capacitor design for reliability and improved efficiency. High temperature Class F insulation system. Requires 30 MFD, 370 VAC capacitor, separately mounted – not supplied.

SINGLE PHASE • RIGID BASE • TENV

HP	RPM 60 Hz	NEMA Frame	Catalog Number	Disc. Sym.	App. Wgt. (lbs.)	Voltage	Over- load Prot.	F.L. Amps 230V	"C" Dim. (Inches)
1/2	3450	56CZ	113939	A	42	230	None	4.5	13.07

QUICK REFERENCE

SINGLE PHASE MOTORS.....	Page 8
SINGLE PHASE C FACE MOTORS	22
WASHGUARD MOTORS.....	30
JET PUMP MOTORS.....	48

LEESON® POULTRY MOTORS SINGLE AND THREE PHASE

FEED-AUGER DRIVE MOTORS DUST-TIGHT

Dust-tight, capacitor start motor with your choice of field proven electronic or protected mechanical starting switch—both eliminate damage caused when motor is over-speeded by obstructed auger.



Ball bearing, heavy duty industrial quality designs for high overload capacity. Side mounted conduit box. Flange mounts directly to drive assembly. Fully gasketed to keep out feed dust. Has screw driver slot in rear shaft. Continuous duty, with manual thermal overload protection. Motors of 3/4 HP and less in the two adjacent charts have shaft of 1/2" diameter x 1 1/2" length, with flat; motors 1 HP and larger have 5/8" diameter x 1.97" length, with key.

SINGLE PHASE • TEFC • 60 HERTZ

HP	RPM 60 Hz	NEMA Frame	Catalog Number	Disc. Sym.	App. Wgt. (lbs.)	Voltage	Over- load Prot.	F.L. Amps 230V	"C" Dim. (Inches)
1/3	1725	48YZ	101159	A	21	115/230	Man.	3.1	10.47
	1725	48YZ	101435 [®]	A	21	115/230	Man.	3.1	10.47
1/2	1725	48YZ	101120	A	22	115/208-230	Man.	4.0	10.72
	1725	48YZ	101436 [®]	A	22	115/208-230	Man.	4.0	10.47
3/4	1725	48YZ	101119	A	24	115/208-230	Man.	5.4	11.47
	1725	48YZ	101437 [®]	A	28	115/230	Man.	5.4	11.47
1	1725	56YZ	112615	A	35	115/230	Man.	7.0	12.11
	1725	56YZ	113302 [®]	A	35	115/208-230	Man.	7.0	12.61
1 1/2	1725	56YZ	113280 [☆]	A	47	115/208-230	Man.	6.5	13.62
	1725	56YZ	113301 ^{☆®}	A	44	115/230	Man.	6.5	13.62

SINGLE PHASE • TEFC • 50 HERTZ

HP	RPM 50 Hz	NEMA Frame	Catalog Number	Disc. Sym.	App. Wgt. (lbs.)	Voltage	Over- load Prot.	F.L. Amps 220V	"C" Dim. (Inches)
1/2	1425	48YZ	101643 [®]	A	26	110/220	Man.	4.0	11.47
3/4	1425	48YZ	101644 [®]	A	30	110/220	Man.	5.8	12.22
1	1425	56YZ	113906 [®]	A	39	110/220	Man.	6.4	12.61
1 1/2	1425	56YZ	113907 [®]	A	48	110/220	Man.	8.6	13.61

HATCHERY AND INCUBATOR FAN MOTORS



Cat. No. 101341



Cat. No. 114102

General Specifications:
Capacitor-type replacement motors for hatchery and incubator fan motors.

Catalog number 101341 is a permanent split capacitor motor for fan on shaft incubator fans. Band mounted, with 1" long extended through bolts for fan shroud. Shaft diameter 1/2" by 2 1/4", with full length flat. Connections in end of motor through 1/2"-14 NPT tap. UL Listed thermal overload. 15 MFD, 3700 run capacitor shipped loose with motor.

SINGLE PHASE • TEAO

HP	RPM 60 Hz	NEMA Frame	Catalog Number	Disc. Sym.	App. Wgt. (lbs.)	Voltage	Over- load Prot.	F.L. Amps 230V	"C" Dim. (Inches)
1/4	1625	48Y	101341	A	17	115/230	Auto.	1.4	8.93
1/2- 0.22	1725/ 1140	56H	114102	A	33	115	Auto.	9.3-5.6	11.81

Catalog number 114102 is a split phase two-speed motor, dust-tight and totally enclosed for belt driven hatchery cooling fans. Resilient base. With UL Listed automatic thermal overload. Requires no capacitor.

Mechanical Features:
Double shielded ball bearings permanently lubricated with Exxon POLYREX® EM lubricant having a temperature range of -40°F to +320°F and special formulation for extra long life and moisture resistance.

■ Combination 56HZ base has mounting holes for NEMA 56 and 143-5T and a standard NEMA 145T frame shaft of 7/8" diameter.
 ❖ These motors have a 1.5 continuous duty service factor, 3 HP continuous.
 ▶ IEC frame. See page 310 for dimensions.
 ☆ Capacitor start/capacitor run design for reduced amperage, others are capacitor start/induction run.
 ® Mechanical centrifugal starting switch with overspeed protection, others have electronic switch.
 ❖❖ F.L. Amps listed are for high speed and low speeds, respectively, at 115 volts.



Signature Series TEFC
FARM DUTY/AGRICULTURE
 115, 208 & 230 VOLTS • 1-PHASE
 FOOT MOUNT • OVERLOAD PROTECTION
 1/3 TO 10 HP

Features:

- Two designs to choose from: High Torque (HT) and Extra High Torque (EHT)
- Fully gasketed construction and shaft slingers for operation in dirty environments
- Manual reset thermal protector
- Condensate drains
- Continuous duty
- Warranty: 18 months from date of manufacture and 12 months from date of installation which ever period expires first.
- Made in U.S.A.



Applications:

High Torque - HT

Feeders, conveyors, fans, compressors, spray washers, grinders, elevators, pumps and other demanding agricultural applications that require high starting torque.

Extra High Torque - EHT

Silo unloaders, barn cleaners, bunk feeders, conveyors, and other machinery requiring extra high starting torque in demanding farm duty environments. Motors have 300% and greater starting torque.

HIGH TORQUE - HT

HP	SYN RPM	Frame	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	Mult Sym
1/3	1800	56	1.15	115/208-230	SRF4S0.33T1C6028AP7TP1	LM24789	ML	24	AG-1
1/2	1800	56	1.15	115/208-230	SRF4S0.5T1C6028AP7TP1	LM24790	ML	25	AG-1
3/4	1800	56	1.15	115/208-230	SRF4S0.75T1C6028AP7TP1	LM24791	ML	30	AG-1
1	1800	56	1.15	115/208-230	SRF4S1T1C6028AP7TP1	LM24792	ML	32	AG-1
	1800	143T	1.15	115/208-230	SSF4S1T1C6028AP7TP1	LM24793	ML	35	AG-1
1 1/2	1800	56H*	1.15	115/208-230	SRF4S1.5T1B6028AP7TP1	LM24794	ML	41	AG-1
	1800	145T	1.15	115/208-230	SSF4S1.5T1B6028AP7TP1	LM24795	ML	42	AG-1
2	1800	182T	1.15	115/230	SS182F4S2T1C6027AP7TP1	LM24796	ML, D - 131514	64	AG-1
3	1800	184T	1.15	230	SS184F4S3T1C66AP7TP1	LM24797	ML, D - 131542	92	AG-1
5	1800	184T	1.15	230	SSF4S5T1B66AP7TP1	LM24798	ML, D - 131543	90	AG-1
7 1/2	1800	215T	1.15	230	SS215F4S7.5T1B66AP7TP1	LM24799	ML	130	AG-1

EXTRA HIGH TORQUE - EHT

HP	SYN RPM	Frame	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	Mult Sym
2	1800	182TZ	1.15	115/230	SS182F4S2TZ1C6027AP8TP1-1	LM24800	ML, D - 131541	67	AG-1
3	1800	184T	1.15	230	SS184F4S3T1C66AP8TP1	LM24801	ML, D - 131542	85	AG-1
5	1800	184T	1.15	208-230	SSF4S5T1B6008AP8TP1	LM24802	ML	125	AG-1
	1800	213TZ	1.15	230	SS213F4S5TZ1B66AP8TP1-1	LM24803	ML	126	AG-1
7 1/2	1800	215TZ	1.15	230	SS215F4S7.5TZ1B66AP8TP1-1	LM24804	ML	125	AG-1
10	1800	215T	1.00	230	SSF4S10T1B66AP8TP1	LM24805	ML	150	AG-1

*56H, 143T and 145T Combination Base with 12 mounting holes.

Prices and data subject to change without notice.

Product numbers in red are STOCK items.

Signature Series AERATION FAN, HVAC
 115 & 230 VOLTS • 1-PHASE
 FOOT MOUNT • OVERLOAD PROTECTION
 1 TO 3 HP



Features:

- Totally Enclosed, Air Over
- Capacitor start design provides high starting torque
- 18" leads for ease of connection
- Shaft has keyway and 1/4-20 UNC tapped hole
- Double sealed ball bearings for maintenance free operation.
- Warranty: 18 months from date of manufacture and 12 months from date of installation which ever period expires first.

Applications:

Direct drive vane axial fans. These TEAO motors must be mounted in airstream for proper cooling.

*56H, 143T and 145T Combination Base with 12 mounting holes.

HP	SYN RPM	Frame	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	Mult Sym
1	3600	56Z	1.15	115/230	SRA2S1TZ1C6027L10MB6TP2-1	LM24786	AT	29	AG-1
1 1/2	3600	143TZ*	1.15	115/230	SSA2S1.5TZ1C6027L10MB6TP2-1	LM24787	AT	35	AG-1
3	3600	145TZ*	1.15	230	SS145A2S3TZ1B66L10MB6TP2-1	LM24788	AT	52	AG-1

Signature Series AUGER DRIVE
 115, 208 & 230 VOLTS • 1-PHASE
 N-FLANGE FOOTLESS • OVERLOAD PROTECTION
 1/3 TO 1-1/2 HP



Features:

- Totally Enclosed, Fan Cooled
- NEMA "N", two bolt flange mounting
- Shafts:
 3/4 HP & smaller - 1/2" dia. x 1-1/2" long with flat
 1 HP & larger - 5/8" dia. x 2" long with key
- Continuous duty
- Fully gasketed, side mounted terminal box
- Mechanical start switch protected from overspeeded auger drive
- Extended fan-end shaft with flats for manually jogging auger drive
- Warranty: 18 months from date of manufacture and 12 months from date of installation which ever period expires first.



Applications:

Replacement motors for poultry feed auger drive systems. Bolts to existing gearbox for easy installation.

HP	SYN RPM	Frame	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	Mult Sym
1/3	1800	48N	1.00	115/230	SPF4S0.33TADN1C6027TP1	LM24462	ML	23	AG-1
1/2	1800	48N	1.00	115/230	SPF4S0.5TADN1C6027TP1	LM24463	ML	23	AG-1
3/4	1800	56NZ	1.00	115/208-230	SRF4S0.75TZADN1C6028TP1-1	LM24812	ML	31	AG-1
1	1800	56NZ	1.00	115/208-230	SRF4S1TZADN1C6028TP1-1	LM24813	ML	32	AG-1
1 1/2	1800	56NZ	1.00	115/208-230	SRF4S1.5TZADN1C6028TP1-1	LM24814	ML	41	AG-1

Prices and data subject to change without notice.

Product numbers in red are STOCK items.



Signature Series CROP DRYER

230 VOLTS • 1-PHASE & 208-220/440 VOLTS • 3-PHASE
 FOOT MOUNT • OVERLOAD PROTECTION
 3 TO 15 HP

Features:

- Dripproof/Air Over, continuous duty
- Maintenance-free double sealed ball bearings
- Keyed shaft with 1/4-20 UNC tapped hole in end
- 40" long leads for ease of installation (1-phase)
- 30" long leads exit elbow connector (3-phase)
- Fully gasketed terminal box
- Special rotor balance for reduced vibration
- Epoxy coated rotor
- Warranty: 18 months from date of manufacture and 12 months from date of installation which ever period expires first.
- Frame mounted capacitors on LM24778-80.
Capacitors shipped loose on LM24781-82.
- Extra nameplate included for remote mounting



Applications:

Crop dryers with air over/fan on shaft designs.

SINGLE PHASE

HP	SYN RPM	Frame	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	Mult Sym
3 - 4 1/2	3600	145TZ	1.00	230	SSD2S3-4.5TZ1B66QS10-1	LM24778	AT	46	AG-1
5 - 7	3600	184TZ	1.00	230	SS184D2S5-7TZ1C66QS11-1	LM24779	TT, D - 131847	76	AG-1
7 - 10	3600	184TZ	1.00	230	SSD2S7-10TZ1B66QS11-1	LM24780	TT	102	AG-1
7 - 9	3600	184TZ	1.00	230	SSD2S7-9TZ1C66QS11-1	LM24781	TT, D - 131849	88	AG-1
10 - 15	3600	215TZ	1.00	230	SS215D2S10-15TZ1C66QS11-1	LM24782	TT	135	AG-1



Signature Series GRAIN STIRRING

115/208-230 VOLTS • 1-PHASE
 FOOT MOUNT
 1-1/2 HP

Features:

- TEFC, continuous duty
- Maintenance-free double sealed ball bearings
- 7/8" diameter shaft
- Fully gasketed construction and fan/fan guard on shaft end keep grain dust out of motor
- Warranty: 18 months from date of manufacture and 12 months from date of installation which ever period expires first.



Applications:

Grain stirring systems inside grain bins.

HP	SYN RPM	Frame	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	Mult Sym
1 1/2	1800	56HZ	1.15	115/208-230	SRF4S1.5TZ1B6028AP9-2	LM24521		47	AG-1

Prices and data subject to change without notice.

Product numbers in red are STOCK items.